

## for Commercial Suspended Ceilings

Flexible sprinkler hose with threaded end fittings are for use in commercial suspended ceilings. The flexible hoses are to be installed according to the manufacturer's directives. Unless indicated, the hoses have a rated working pressure of 175 psi (1205 kPa).

### Models SPB, SPNB, SPWB

<i>Model</i>	<i>NPT in.</i>	<i>Hose Assembly length ft (m)</i>	<i>Equivalent Length of 1 in. Schedule 40 Pipe, ft (m)</i>
Rapidrop® -SPB-01A-NPT	1/2	2.5 (0.7)	14.6 (4.5)
Rapidrop® -SPB-02A-NPT	1/2	4 (1.2)	28.0 (8.5)
Rapidrop® -SPB-03A-NPT	1/2	5 (1.5)	50.2 (15.3)
Rapidrop® -SPB-04A-NPT	1/2	6.2 (1.8)	53.5 (16.3)
Rapidrop® -SPB-05A-NPT	1/2	8.3 (2.5)	67.1 (20.4)
Rapidrop® -SPNB-01A-NPT	1/2	2.5 (0.7)	14.6 (4.5)
Rapidrop® -SPNB-02A-NPT	1/2	4 (1.2)	28.0 (8.5)
Rapidrop® -SPNB-03A-NPT	1/2	5 (1.5)	50.2 (15.3)
Rapidrop® -SPNB-04A-NPT	1/2	6.2 (1.8)	53.5 (16.3)
Rapidrop® -SPNB-05A-NPT	1/2	8.3 (2.5)	67.1 (20.4)
Rapidrop® -SPWB-01A-NPT	1/2	2.5 (0.7)	14.6 (4.5)
Rapidrop® -SPWB-02A-NPT	1/2	4 (1.2)	28.0 (8.5)
Rapidrop® -SPWB-03A-NPT	1/2	5 (1.5)	50.2 (15.3)
Rapidrop® -SPWB-04A-NPT	1/2	6.2 (1.8)	53.5 (16.3)
Rapidrop® -SPWB-05A-NPT	1/2	8.3 (2.5)	67.1 (20.4)
Rapidrop® -SPB-01B-NPT	3/4	2.5 (0.7)	20.7 (6.3)
Rapidrop® -SPB-02B-NPT	3/4	4 (1.2)	32.1 (9.8)
Rapidrop® -SPB-03B-NPT	3/4	5 (1.5)	48.4 (14.7)

Rapidrop® -SPB-04B-NPT	3/4	6.2 (1.8)	56.6 (17.2)
Rapidrop® -SPB-05B-NPT	3/4	8.3 (2.5)	77.1 (23.5)
Rapidrop® -SPNB-01B-NPT	3/4	2.5 (0.7)	20.7 (6.3)
Rapidrop® -SPNB-02B-NPT	3/4	4 (1.2)	32.1 (9.8)
Rapidrop® -SPNB-03B-NPT	3/4	5 (1.5)	48.4 (14.7)
Rapidrop® -SPNB-04B-NPT	3/4	6.2 (1.8)	56.6 (17.2)
Rapidrop® -SPNB-05B-NPT	3/4	8.3 (2.5)	77.1 (23.5)
Rapidrop® -SPWB-01B-NPT	3/4	2.5 (0.7)	20.7 (6.3)
Rapidrop® -SPWB-02B-NPT	3/4	4 (1.2)	32.1 (9.8)
Rapidrop® -SPWB-03B-NPT	3/4	5 (1.5)	48.4 (14.7)
Rapidrop® -SPWB-04B-NPT	3/4	6.2 (1.8)	56.6 (17.2)
Rapidrop® -SPWB-05B-NPT	3/4	8.3 (2.5)	77.1 (23.5)

1 in. nominal dia. flexible metal hose for providing a connection to automatic sprinklers in commercial suspended ceilings. Approval is limited for use in commercial suspended ceilings. Approval is limited for use in commercial suspended ceilings with a bracket system manufactured by Rapidrop Limited.

The code of information for these model designations is as follows:

Marking	Description
Rapidrop®	Company Name & Trademark
SPB	The hose is threaded to a nipple on the inlet end and threaded to a reducer at the outlet.
SPNB	The hose is threaded to a nipple on the inlet end and the reducer is brazed to the flexible hose at the outlet

SPWB	The hose is brazed to a nipple on the inlet end and brazed to a reducer at the outlet
01 02 03 04 05	Flexible Hose Lengths: 01 = 780 mm 02 = 1,220 mm 03 = 1,540 mm 04 = 1,880 mm 05 = 2,500 mm
A	1/2 in. NPT
B	3/4 in. NPT

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved