

## Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Model OSF200, OSF250, OSF300, OSG300

<i>Model No.</i>	<i>Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>End Connections</i>
OSF200	Resilient Seated Gate Valves	2-1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	200 psi (1380 kPa)	Flange x Flange (ANSI, BS10, BS4505, JIS B2212, JIS B2213)
OSF250	Resilient Seated Gate Valves	4, 6, 8 (100, 150, 200)	250 psi (1725 kPa)	Flange x Flange (ANSI)
OSF300	Resilient Seated Gate Valves	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	300 psi (2068 kPa)	Flange x Flange (ANSI, ISO, JIS)
OSG300	Resilient Seated Gate Valves	2-1/2, 3, 4, 5, 6, 8, 10, 12 (65, 80, 100, 125, 150, 200, 250 and 300)	300 psi (2068 kPa)	Groove x Groove

<b>Company Name:</b>	Rapidrop Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved