

Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

104GG, 104FG, 104FF, 1047MJ

<i>Model No.</i>	<i>Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>End Connections</i>
104GG	Resilient Seated Gate Valves	2-1/2, 3, 4, 6, 8, 10 (65, 80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Groove x Groove
104GG	Resilient Seated Gate Valves	12 (300) NPS	250 psi (1725 kPa)	Groove x Groove
104FG	Resilient Seated Gate Valves	2-1/2, 3, 4, 6, 8, 10 (65, 80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Flange x Groove
104FG	Resilient Seated Gate Valves	12 (300) NPS	250 psi (1725 kPa)	Flange x Groove
104FF	Resilient Seated Gate Valves	2, 2-1/2, 3, 4, 6, 8, 10 (50, 65, 80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Flange x Flange
104FF	Resilient Seated Gate Valves	12 (300) NPS	250 psi (1725 kPa)	Flange x Flange
104MJ	Resilient Seated Gate Valves	3, 4, 6, 8, 10 (80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Mechanical Joint x Mechanical Joint
104MJ	Resilient Seated Gate Valves	12 (300) NPS	250 psi (1725 kPa)	Mechanical Joint x Mechanical Joint

Company Name:	Rapidrop Global Limited
Company Address:	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
Company Website:	http://www.rapidrop.com
Listing Country:	United Kingdom
Certification Type:	FM Approved