

Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

PIV200, PIV300, PIV300FJ, PIV300MJ

<i>Model No.</i>	<i>Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>End Connections</i>
PIV200	Resilient Seated Gate Valves	2-1/2, 3, 4, 6, 8, 10, 12 (65, 80, 100, 150, 200, 250, 300)	200 (1380)	Flanged × Flanged (ANSI, BS10, BS4505, JIS B2212, JIS B2213)
PIV300 *	Resilient Seated Gate Valves	4, 5, 6, 8, 10, 12 (100, 125, 150, 200, 250 and 300)	300 (2070)	Flange × Flange (ANSI, ISO, JIS)
PIV300FJ *	Resilient Seated Gate Valves	4, 5, 6, 8, 10, 12 (100, 125, 150, 200, 250 and 300)	300 (2070)	Flange × Mechanical Joint
PIV300MJ *	Resilient Seated Gate Valves	4, 5, 6, 8, 10, 12 (100, 125, 150, 200, 250 and 300)	300 (2070)	Mechanical Joint

* Available with an indicator post flange.

Company Name:	Rapidrop Limited
Company Address:	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
Company Website:	http://www.rapidrop.com
Listing Country:	United Kingdom
Certification Type:	FM Approved