



HLXS.EX15412 Butterfly Valves

[Page Bottom](#)

Butterfly Valves

[See General Information for Butterfly Valves](#)

RAPIDROP GLOBAL LTD

EX15412

RUTLAND BUSINESS PARK
NEWARK RD
PETERBOROUGH, PE1 5WA UNITED KINGDOM

Model BT175 bronze body, threaded ends, sizes 1, 1-1/4, 1-1/2, 2, 2-1/2 in., for a rated pressure of 175 psi.

Model BG175 bronze body, grooved-ends, sizes 2, 2-1/2 in., for a rated pressure of 175 psi.

Models BT175, BG175 valves may be factory supplied with internal supervisory tamper switches intended for indoor/outdoor use.

Model DW175 ductile iron wafer body, sizes 2-1/2, 3, 4, 6, 8 in. for a rated pressure of 175 psi.


Model DG175 coated ductile iron body, grooved-ends, sizes 2-1/2, 3, 4, 6, 8 in. for a rated pressure of 175 psi.

Models DW175, DG175 valves may be factory supplied with internal supervisory tamper switches intended for indoor use only.

Model HPW300 wafer body and Model HPG300 grooved body in 2-1/2, 3, 4, 6 and 8 in. sizes for rated pressure of 300 psi, supplied with internal supervisory tamper switches intended for indoor/outdoor use.

Model HRW300 wafer body and Model HRG300 grooved body in 2-1/2, 3, 4, 6 and 8 in. sizes for rated pressure of 300 psi, supplied with internal supervisory tamper switches intended for indoor/outdoor use.



Trademark and/or Tradename:  , "Rapidrop"

[Last Updated](#) on 2011-08-23

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".