

**HMER.EX15304  
Check Valves**[Page Bottom](#)

---

**Check Valves**[See General Information for Check Valves](#)**RAPIDROP GLOBAL LTD**

EX15304

RUTLAND BUSINESS PARK


NEWARK RD

PETERBOROUGH, PE1 5WA UNITED KINGDOM

**Swing type**, Fig. CVDDW175, 4, 6, 8, 10 and 12 size wafer style check valves rated working pressure of 175 psig (1210 kpa) vertical installation.

Model FCG300, sizes 2, 2-1/2, 3, 4, 5 and 6 in., with resilient seat size for rated pressure of 300 psig horizontal and vertical installation.

CVF300, sizes 2, 2-1/2, 3, 4, 5, 6, 8, 10 and 12 in. (50.8, 63.5, 76.2, 101.6, 127, 139.7, 203.2, 254 and 304.8mm), with rubber faced checks for working pressures not exceeding 300 psig (2068Kpa). Installation - horizontal or vertical.

Trademark and/or Tradename:  , "Rapidrop"[Last Updated](#) on 2011-02-02

---

[Questions?](#)[Print this page](#)[Notice of Disclaimer](#)[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".