



VENF.EX4957 Flexible Sprinkler Hose with Fittings

[Page Bottom](#)

Flexible Sprinkler Hose with Fittings

[See General Information for Flexible Sprinkler Hose with Fittings](#)**RAPIDROP GLOBAL LTD**

RUTLAND BUSINESS PARK


NEWARK RD

PETERBOROUGH, PE1 5WA UNITED KINGDOM

EX4957

Model	Rated Pressure, psig	Max Ambient Temp, °F	Nom Inlet by Outlet Size, in.	Assembly Length, ft (mm)	Max No. of 90° Bends	Min Bend Radius, in.	Equivalent Length of 1 in. Schedule 40 Steel Pipe (C = 120), ft	Flexibility Type
RAP-SP-01AS unbraided	175	225	1x1/2	2.3 (700)	2	4	18	Limited
RAP-SP-01A unbraided	175	225	1x1/2	2.6 (780)	2	4	27	Limited
RAP-SP-02AS unbraided	175	225	1x1/2	3.3 (1000)	3	4	44	Limited
RAP-SP-02A unbraided	175	225	1x1/2	4.0 (1220)	3	4	53	Limited
RAP-SP-03A unbraided	175	225	1x1/2	5.1 (1540)	3	4	68	Limited
RAP-SP-04A unbraided	175	225	1x1/2	6.0 (1830)	3	4	73	Limited
RAP-SP-01BS unbraided	175	225	1x3/4	2.3 (700)	2	4	32	Limited
RAP-SP-01B unbraided	175	225	1x3/4	2.6 (780)	2	4	33	Limited
RAP-SP-02BS unbraided	175	225	1x3/4	3.3 (1000)	3	4	48	Limited
RAP-SP-02B unbraided	175	225	1x3/4	4.0 (1220)	3	4	55	Limited
RAP-SP-03B unbraided	175	225	1x3/4	5.1 (1540)	3	4	63	Limited
RAP-SP-04B unbraided	175	225	1x3/4	6.0 (1830)	3	4	76	Limited

These flexible sprinkler hose with fittings are intended to be installed with the B-13 and A-10 bracket combination in accordance with the manufacturer's installation instructions dated March 04, 2009.

Trademark and/or Tradename: , "Rapidrop"[Last Updated](#) on 2012-01-23[Questions?](#)[Print this page](#)[Notice of Disclaimer](#)[Page Top](#)

© 2012 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".