



HLCV.EX15306 Strainers, Pipeline

[Page Bottom](#)

Strainers, Pipeline

[See General Information for Strainers, Pipeline](#)

RAPIDROP GLOBAL LTD

EX15306


RUTLAND BUSINESS PARK

NEWARK RD

PETERBOROUGH, PE1 5WA UNITED KINGDOM

Strainers, "Y" type, Models YSG175 (Grooved), YSF175 (Flanged), in sizes 2-1/2, 3, 4, 5, 6, 8, 10 and 12 in. for rated pressure of 175 psig. Loss of head will approximate 8.3 psi for the 2-1/2 in. size at 224 GPM, 12.2 psi for the 3 in. size at 350 GPM, 7.2 psi for the 4 in. size at 600 GPM, 5.9 psi for the 5 in. size at 948 GPM, 7.3 psi for the 6 in. size at 1351 GPM, 5.2 psi for the 8 in. size at 2400 GPM and 5.2 psi for the 10 in. size at 3600 GPM and 7.8 psi for the 12 in. size at 5288 GPM.



Trademark and/or Tradename:  , "Rapidrop"

[Last Updated](#) on 2011-02-02

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[© 2012 UL LLC](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2012 UL LLC".