

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models 104GG, 104FG, 104FF, 104MJ

<i>Model No.</i>	<i>Description</i>	<i>Nominal Pipe Size, in.</i>	<i>Max Working Pressure, psi (kPa)</i>	<i>End Connections</i>
104GG	Resilient Seated Gate Valves	2-1/2, 3, 4, 6, 8, 10 (65, 80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Groove x Groove
104GG	Resilient Seated Gate Valves	12, 14, 16 (300, 350, 400) NPS	250 psi (1725 kPa)	Groove x Groove
104FG	Resilient Seated Gate Valves	2-1/2, 3, 4, 6, 8, 10 (65, 80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Flange x Groove
104FG	Resilient Seated Gate Valves	12, 14, 16 (300, 350, 400) NPS	250 psi (1725 kPa)	Flange x Groove
104FF	Resilient Seated Gate Valves	2, 2-1/2, 3, 4, 6, 8, 10 (50, 65, 80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Flange x Flange
104FF	Resilient Seated Gate Valves	12, 14, 16 (300, 350, 400) NPS	250 psi (1725 kPa)	Flange x Flange
104MJ	Resilient Seated Gate Valves	3, 4, 6, 8, 10 (80, 100, 150, 200, 250) NPS	300 psi (2070 kPa)	Mechanical Joint x Mechanical Joint
104MJ	Resilient Seated Gate Valves	12, 14, 16 (300, 350, 400) NPS	250 psi (1725 kPa)	Mechanical Joint x Mechanical Joint

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved