

## Indicating Valves, Butterfly or Ball Type

Design features provide a dependable visible indication of the open position even at a distance. If excessive force is applied to the handle, weakness-joints will break so as to preserve correct orientation between indicator and valve position. Valve and indicator parts are so designed that they can be assembled only one way, always to give correct indication. All FM Approved indicating valves turn clockwise to shut. They are small, lightweight, and, because of a resilient seat, are easy to operate. They are not subject to sticking or dropped gates. They are not recommended for throttling service. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models 202, 215, 216, 217, 217 PN16

<b>Model Number</b>	<b>Product Type</b>	<b>Nominal Pipe Size, in</b>	<b>Maximum Working Pressure, psi (kPa)</b>	<b>Remarks</b>
215	Butterfly Valve, Wafer Body	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a, b, c
217	Butterfly Valve, Lug Body	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a, b, c, d
216	Butterfly Valve, Grooved Ends	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 76.1, 139.7, 165.1 mm	300 (2070)	a, b, c
217 PN16	Butterfly Valve, Lug Body	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12	300 (2070)	a, b, c, e
202	Butterfly Valve, Threaded Ends	1, 1-1/4, 1-1/2, 2	175 (1205)	a, b, c, f

#### Remarks:

- a. Available with dual supervisory switches.
- b. FM Approved for indoor and outdoor service.
- c. FM Approved for aboveground installations only.
- d. Flange standards ASME B16.1 Class 125, ASME B16.5 Class 150,
- e. Flange standards EN 1092 PN10/16, JIS B2212 10K, BS 10 Table D/E, and AS2129 Table D/E.
- f. NPT or BSPT threads.

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved