

## Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Fig 113.2GG

Resilient Seated Gate Valves. 2 through 12 in. NPS. Valves have a rated working pressure of 232 psi (1600 kPa). Available with the following end connections.

Model	Size, in. (mm)	End Connection
Fig 113.2GG	2, 2 1/2, 3, 4, 6, 8, 10, 12 (50, 65, 80, 100, 150, 200, 250, 300)	Groove x Groove (AWWA C606)

<b>Company Name:</b>	Rapidrop Global Limited
<b>Company Address:</b>	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
<b>Company Website:</b>	<a href="http://www.rapidrop.com">http://www.rapidrop.com</a>
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United Kingdom
<b>Certification Type:</b>	FM Approved