

Indicating Valves, Butterfly or Ball Type

Design features provide a dependable visible indication of the open position even at a distance. If excessive force is applied to the handle, weakness-joints will break so as to preserve correct orientation between indicator and valve position. Valve and indicator parts are so designed that they can be assembled only one way, always to give correct indication. All FM Approved indicating valves turn clockwise to shut. They are small, lightweight, and, because of a resilient seat, are easy to operate. They are not subject to sticking or dropped gates. They are not recommended for throttling service. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

Models 220, 221

Model Number	Product Type	Nominal Pipe Size, inch (mm)	Rated Working Pressure, psi (kPa)	Remarks
220	Butterfly Valve, Wafer by Wafer End Connections	2-1/2, 3, 4, 5, 6, 8 (65, 80, 100, 125,150, 200)	300 (2070)	a, b, c
221	Butterfly Valve, Groove x Groove End Connections	2-1/2, 3, 4, 5, 6, 8 (65, 80, 100, 125,150, 200)	300 (2070)	a, b, c

Remarks:

- a. Available with or without supervisory switches.
- b. FM Approved for indoor and outdoor service.
- c. FM Approved for aboveground installations only.

Company Name:	Rapidrop Global Limited
Company Address:	Rutland Business Park, Newark Rd, Peterborough PE15WA, United Kingdom
Company Website:	http://www.rapidrop.com
New/Updated Product Listing:	No
Listing Country:	United Kingdom
Certification Type:	FM Approved