

## HMER.EX15304 Check Valves

[Page Bottom](#)

### Check Valves

[See General Information for Check Valves](#)

**RAPIDROP GLOBAL LTD**

EX15304

RUTLAND BUSINESS PARK  
NEWARK RD  
PETERBOROUGH, PE1 5WA UNITED KINGDOM

**Swing type**, Fig. CVDDW175, 4, 6, 8, 10 and 12 size wafer style check valves rated working pressure of 175 psig (1210 kpa) vertical installation.

CVF300, sizes 2, 2-1/2, 3, 4, 5, 6, 8, 10 and 12 in. (50.8, 63.5, 76.2, 101.6, 127, 139.7, 203.2, 254 and 304.8 mm), with rubber faced checks for working pressures not exceeding 300 psig (2068 Kpa). Installation - horizontal or vertical.

Models 304-060 (2"), 304-073 (2-1/2"), 304-076 (2-1/2"), 304-089 (3"), 304-114 (4"), 304-139 (5"), 304-141 (5"), 304-165 (6"), 304-168 (6"), 304-219 (8"), in. (DN 65, DN150), with resilient seat for rated working pressures of 350 psig horizontal and vertical installation.

Models 305-050 (2"), 305-065 (2-1/2"), 305-080 (3"), 305-100 (4"), 305-125 (5"), 305-150 (6"), 305-200 (8") in. (DN 65, DN150), with resilient seat for rated working pressures of 350 psig horizontal and vertical installation.

**Swing-type check valves**, Models Fig.302 PN16, Fig.302, sizes 2, 2.5, 3, 4, 6, 8, 10 and 12 in. with rubber faced checks, rated for 300 psi, horizontal or vertical installation.

**Swing-type check valve**, Model Fig.301, sizes 2, 2.5, 3, 4, 6, 8, 10 and 12 in. with rubber faced checks, rated for 300 psi, horizontal or vertical installation.



Trademark and/or Tradename:  , "Rapidrop"

[Last Updated](#) on 2017-01-23

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".