

VGYZ.EX15520 Nozzles, Spray Type, Fixed

Page Bottom

Nozzles, Spray Type, Fixed

See General Information for Nozzles, Spray Type, Fixed

RAPIDROP GLOBAL LTD

EX15520

RUTLAND BUSINESS PARK

NEWARK RD

PETERBOROUGH, PE1 5WA UNITED KINGDOM

Nonautomatic Type

Model	Discharge Angle Deg	Discharge Coefficient K	
		K(GPM/(psig) ^{1/2})	K-m(LPM/(kg/cm ²) ^{1/2})
MV-E	65, 80, 90, 100, 110, 120, 140	1.26	18
MV-A	65, 80, 90, 100, 110, 120, 140	1.26	18
MV-AS	65, 80, 90, 100, 110, 120, 140	1.26	18
MV-E	65, 80, 90, 100, 110, 120, 140	1.5	22
MV-A	65, 80, 90, 100, 110, 120, 140	1.5	22
MV-AS	65, 80, 90, 100, 110, 120, 140	1.5	22
MV-E	65, 80, 90, 100, 110, 120, 140	2.1	30
MV-A	65, 80, 90, 100, 110, 120, 140	2.1	30
MV-AS	65, 80, 90, 100, 110, 120, 140	2.1	30
MV-E	65, 80, 90, 100, 110, 120, 140	2.5	35
MV-A	65, 80, 90, 100, 110, 120, 140	2.5	35
MV-AS	65, 80, 90, 100, 110, 120, 140	2.5	35
MV-E	65, 80, 90, 100, 110, 120, 140	2.9	41
MV-A	65, 80, 90, 100, 110, 120, 140	2.9	41
MV-AS	65, 80, 90, 100, 110, 120, 140	2.9	41
MV-E	65, 80, 90, 100, 110, 120, 140	3.6	51
MV-A	65, 80, 90, 100, 110, 120, 140	3.6	51
MV-E	65, 80, 90, 100, 110, 120, 140	4.5	64
MV-A	65, 80, 90, 100, 110, 120, 140	4.5	64
MV-E	65, 80, 90, 100, 110, 120, 140	5.5	79
MV-A	65, 80, 90, 100, 110, 120, 140	5.5	79
MV-E	65, 80, 90, 100, 110, 120, 140	6.4	91
MV-A	65, 80, 90, 100, 110, 120, 140	6.4	91
MV-E	65, 80, 90, 100, 110, 120, 140	7.2	102
MV-A	65, 80, 90, 100, 110, 120, 140	7.2	102
MV-B	65, 80, 90, 100, 110, 120, 140	7.2	102
MV-BS	65, 80, 90, 100, 110, 120, 140	K(GPM/(psig) ^{0.5}) 1.26; K-m(LPM/(kg/cm ²) ^{0.5}) 18	
MV-BS	65, 80, 90, 100, 110, 120, 140	K(GPM/(psig) ^{0.5}) 1.5; K-m(LPM/(kg/cm ²) ^{0.5}) 22	
MV-BS	65, 80, 90, 100, 110, 120, 140	K(GPM/(psig) ^{0.5}) 2.1; K-m(LPM/(kg/cm ²) ^{0.5}) 30	

MV-BS	65, 80, 90, 100, 110, 120, 140	$K(\text{GPM}/(\text{psig})^{0.1/2})$ 2.5; $K\text{-m}(\text{LPM}/(\text{kg}/\text{cm}^2)^{0.1/2})$ 35	
MV-BS	65, 80, 90, 100, 110, 120, 140	$K(\text{GPM}/(\text{psig})^{0.1/2})$ 2.9; $K\text{-m}(\text{LPM}/(\text{kg}/\text{cm}^2)^{0.1/2})$ 41	
HV-AS	80	1.26	18
HV-AS	75	1.54	22
HV-AS	120	1.61	23
HV-AS	100	1.82	26
HV-AS	90	2.24	32
HV-AS	115	2.94	42
HV-BS	80	1.26	18
HV-BS	75	1.54	22
HV-BS	120	1.61	23
HV-BS	100	1.82	26
HV-BS	90	2.24	32
HV-BS	115	2.94	42

Last Updated on 2017-01-10

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

© 2017 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2017 UL LLC".