



Data Sheet 10.44

Issue B



Right Angled Globe Hydrant Valve Model: DRV003

Product Description

Right Angled Globe Hydrant Valves are outlets commonly used on stand pipes, wet pillar hydrant systems or dry riser systems. Right Angled Valve DRV003 is available with PN16 flanged inlet, DN65 Female instantaneous coupling outlet and comes complete with cap & chain.

Working Pressure

Max. working pressure 16 bar (232 psi)
Max. test pressure 22.5 bar (325 psi)

Connections

Inlet

PN16 Flange as per BS EN 1092

Outlet

2 1/2" (DN65) female instantaneous coupling as per BS336

Standards

Manufactured to BS5041 part 2

Features

- Manufactured from LG2 bronze
- Compact design

Material Specifications

No	Description	Materials
1	Handwheel	Cast Iron
2	Stem	Brass
3	Nut	Brass
4	Valve Cap	Brass
5	Valve Cap O-ring	Rubber
6	Nut	Brass
7	Press Plate	LG2
8	Body	LG2
9	Nut M12	Brass
10	Handwheel Gasket	Brass
11	Valve Stem O-ring	Rubber
12	Sealing ring	Rubber
13	Guard Knob	Brass
14	Tag	Brass
15	Cap	Plastic
16	Nut M8	Steel
17	Spring	SS304
18	Cap with Chain	Plastic + Steel

