

RDWFDxxN, RDWFDxxEN

Product Description

Rapidrop Models RDWFDxxN

Saddle-mount. Model RDWFDxxN sizes 2 through 8 inch NPS. 450 psi (3105 kPa) rated working pressure.

Sizes 2 through 4 inch NPS rated for use with Schedule 7, 10 and 40 pipe. Sizes 5, 6 and 8 inch NPS rated for use with Schedule 10 and 40 pipe.

Rapidrop Models RDWFDxxEN,

Saddle-mount. Model RDWFDxxEN sizes DN50 through DN150 mm NPS. 250 psi (1725 kPa) rated working pressure.

Product Specification

Model No	Valve Size	
	in	(mm)
RDWFD20N	2	(50)
RDWFD25N	2 1/2	(65)
RDWFD30N	3	(80)
RDWFD40N	4	(100)
RDWFD50N	5	(125)
RDWFD60N	6	(150)
RDWFD80N	8	(200)
RDWFD20EN	60.3	(N/A)
RDWFD25EN	76.1	(N/A)
RDWFD30EN	88.9	(N/A)
RDWFD40EN	114.3	(N/A)
RDWFD60EN	168.3	(N/A)
RDWFD80EN	219.1	(N/A)

Details

Category	Waterflow Detectors, Vane Type
Class of Work	1042 - Waterflow Detectors(vane type)

Company

Rapidrop Global Limited
Rutland Business Park, Newark Rd, Peterborough PE1 5WA, United Kingdom
<http://www.rapidrop.com>



Member of the FM Global Group

Approval Standard	FM 1042 - Vane-Type Waterflow Alarm Indicators
Certification Type	FM Approved
Listing Country	United Kingdom