

# Model #413

File Number: EX27882

## COMPANY

**RAPIDROP GLOBAL LTD**  
 RUTLAND BUSINESS PARK  
 NEWARK RD  
 PETERBOROUGH, PE1 5WA United Kingdom

## MODEL INFO

#413  
 Single-jacketed

## HOSE INFORMATION

Hose Size, in. (mm)	Service Test Pressure, psig (kPa)	Ratings	Comments	Heat Resistance Type
1-1/2 (38)	250 (1723)	--	EPDM Lining, Synthetic Polyester Jacket	Type 3
2-1/2 (65)	250 (1723)	--	EPDM Lining, Synthetic Polyester Jacket	Type 3

## CONDUCTIVE HEAT EXPOSURE: STEEL BLOCK AT 400°C (752°F)

Hose Size, in. (mm)	Exposure Duration	Avg Leakage Rate @ 150 psi	Max Leakage Rate @ 150 psi
1-1/2 (38)	2 sec	> 20 gpm	> 20 gpm
2-1/2 (65)	2 sec	> 20 gpm	> 20 gpm

## RADIANT HEAT EXPOSURE: 30 KW/M2

Hose Size, in. (mm)	Color/Marking	Exposure Duration	Avg Leakage Rate @ 150psi	Max Leakage Rate @ 150 psi
1-1/2 (38)	White	10 min 20 sec	9 gpm	> 20 gpm
2-1/2 (65)	White	5 min 55 sec	> 20 gpm	> 20 gpm

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2026 UL LLC."